



# C4400 - Interior Latex Semi-Gloss

## Technical Specifications

<b>PRODUCT DESCRIPTION</b>			
C4400 is a 100% acrylic semi-gloss finish designed for applications high traffic areas such as kitchens, bathrooms, and trim. Characterized by exceptional hiding, stain resistance, washability and flow and leveling, C4400's performance is equivalent to the finest alkyd.			
<b>SPECIFICATIONS</b>			
<b>Type:</b>	Acrylic Resin	<b>Dry Time - Touch:</b>	30 Minutes
<b>Sizes:</b>	1's and Quarts	<b>Dry Time - Recoat:</b>	2 to 4 Hours
<b>Bases:</b>	White, Pastel, Midtone, Accent	<b>Full Service:</b>	7 Days
<b>Gloss:</b>	40 - 50% @ 60 <sup>0</sup>	<b>Flash Point:</b>	None
		<b>VOC:</b>	236 - 274 gm/L
		<b>% Solids Volume:</b>	37-38
		<b>Weight Per Gallon:</b>	10.86 +/- .25
<b>PRODUCT USE</b>			
<p style="text-align: center; color: green;"><b>Surface preparation</b></p> <p>Clean surface to remove contaminants such as dirt, dust, oil, grease, wax and rust. Patch holes and cracks, sand smooth and remove sanding dust and spot prime.</p> <p><b>New Plaster &amp; Drywall:</b> Plaster must be completely cured (30 days) before painting. Sand smooth drywall tape joints and other repaired areas. Apply one coat <b>C2000 Interior Latex Primer</b> to entire surface. Finish with one or two coats of <b>C<sup>2</sup> Interior Latex Semi-gloss</b>.</p> <p><b>Previously Painted Surfaces:</b> Remove all loose or peeling paint. Repair damaged surfaces and sand smooth. Dull glossy surfaces. Spot prime with <b>C2000 Interior Latex Primer</b>. When painting over dark colors, best results are achieved by priming entire surface. Finish with one or two coats of <b>C<sup>2</sup> Interior Latex Semi-gloss</b></p> <p><b>New Wood:</b> Sand entire surface and apply one coat of either <b>C2000 Interior Latex</b> or <b>A6000 Interior Alkyd Primer</b>. Allow primer to dry. Sand smooth entire surface. Apply one or two coats of <b>C<sup>2</sup> Interior Latex Semi-gloss</b>.</p>		<p style="text-align: center; color: green;"><b>Application</b></p> <p><b>C4400 Interior Latex Semi-gloss</b> may be applied by roller (no less than 3/8-inch nap), brush (synthetic) or spray.</p> <p><b>Spreading Rate:</b> Product should be applied at a rate of 400 to 450 square feet per gallon. (37 to 42 square meters per 3.78 liters) Overspreading can result in hiding problems.</p> <p><b>Thinning:</b> Do not thin.</p> <p><b>Airless Spray:</b> Use a 12 to 15 mil size tip.</p> <p><b>Cleanup:</b> Clean painting equipment and spills immediately using warm soapy water.</p> <p><b>Limitations: Do not apply if product, air or surface temperature is below 50<sup>0</sup> F (10<sup>0</sup> C) - Keep product from freezing.</b> Product application and surface conditions are beyond the manufacturer's control. Liability, if any, is limited to replacement of product only.</p> <p><b>Disposal:</b> Do not dispose of any paint product or solvent in drains, sewers or municipal garbage. Use all of the paint you purchase or give it to someone who can use it. If disposal is necessary, contact your local C2 dealer for recommendations in your area.</p>	
<b>C2 Paint is formulated without lead or mercury</b>			

Last Update – September 18, 2000.