



# C2200 - Interior Latex Eggshell

## Technical Specifications

### PRODUCT DESCRIPTION

C2200 ProSeries Interior Latex Eggshell is an acrylic fortified low odor, scrubable finish for application in most residential or commercial environments. C2200 ProSeries is specifically formulated to provide maximum coverage, spatterless application, and virtually *invisible touchup*.

### SPECIFICATIONS

<b>Type:</b>	Co-Polymer Acrylic	<b>Dry Time – Touch:</b>	30minutes
<b>Sizes:</b>	1's and 5's	<b>Dry Time – Recoat:</b>	2 to 4 hours
<b>Bases:</b>	White, Pastel, Midtone, Accent	<b>Full Service:</b>	14 days
<b>Gloss:</b>	3 to 5% at 60° 10 to 15% at 85°	<b>Flash Point:</b>	None
		<b>VOC:</b>	73 grams/liter
		<b>% Solids Vol:</b>	36 – 37
		<b>Weight Per Gallon:</b>	11.25 +/- .25 lbs.

### PRODUCT USE

#### Surface Preparation

Clean surface to remove contaminants such as dirt, dust, oil, grease, wax, and rust. Patch holes and cracks, sand smooth and remove sanding dust and spot prime.

**New Plaster & Drywall:** Plaster must be completely cured (30 days) before painting. Sand smooth drywall tape joints and other repaired areas. Apply one coat C<sup>2</sup> ProSeries Interior Latex Primer to entire surface. Finish with one or two coats of C<sup>2</sup> ProSeries Interior Latex Eggshell.

**Previously Painted Surfaces:** Remove all loose or peeling paint. Repair damaged surfaces and sand smooth. Dull glossy surfaces. Spot prime with C<sup>2</sup> ProSeries Interior Latex Primer. When painting over dark colors, best results are achieved by priming entire surface. Finish with one or two coats of C<sup>2</sup> ProSeries Interior Latex Eggshell.

**New Wood:** Sand entire surface and apply one coat of either C<sup>2</sup> ProSeries Interior Latex or Alkyd Primer. Allow primer to dry. Sand smooth entire surface. Apply one or two coats of C<sup>2</sup> ProSeries Interior Latex Eggshell.

#### Application

C2200 ProSeries Interior Latex Eggshell may be applied by roller (no less than 3/8-inch nap), brush (synthetic) or spray.

**Spreading Rate:** Product should be applied at a rate of 400 to 450 square feet per gallon (37 to 42 square meters per 3.78 liters).

**Thinning:** Do not thin.

**Airless Spray:** Use a 12 to 15 mil size tip.

**Cleanup:** Clean painting equipment and spills immediately using warm soapy water.

**Limitations:** Do not apply if product, air or surface temperature is below 50° F (10° C) - Keep product from freezing. Product application and surface conditions are beyond the manufacturer's control. Liability, if any, is limited to replacement of product only.

**Disposal:** Do not dispose of any paint product or solvent in drains, sewers or municipal garbage. Use all of the paint you purchase or give it to someone who can use it. If disposal is necessary, contact your local municipality.

**C<sup>2</sup> ProSeries Paint is formulated without lead or mercury**